

## DINTEX® LG-PE

### Features

- Color: Light Gray Matte
- Hydrolysis resistance
- High M.V.T. rate
- Smooth and soft touch

### Physical Properties

*Properties	Method	Unit	**Value	Note
Thickness		mm	0.025	
Width		mm inch	1524 60	
Color			Light Gray Matte	
M.V.T.	ASTM E96-93BW 23°C/50%R.H.	g/m <sup>2</sup> x24hrs	12000~14000	
M.V.T.	JIS L1099-1993 A-1 (CaCl <sub>2</sub> )40 °C 90% R.H.	g/m <sup>2</sup> x24hrs	2900~3100	
W.P.R.	JIS L1092-1998 B Method	mmH <sub>2</sub> O	Over 10000	
Specific Gravity	ASTM D792		1.22	
Elongation	ASTM D882	%	494	
PE Carrier			Yes	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616