

DINTEX® FT1681S-PE

Features

- White matte
- Anti-static
- Excellent hydrolysis resistance
- Oeko-Tex Standard 100 approval
- Smooth and soft touch
- Not sticky after repeat machine wash and heat-dry

Physical Properties

*Properties	Method	Unit	**Value	Note
Thickness		mm	0.020	
Width		mm inch	1524 60	
Color			White matte	
M.V.T.	ASTM E96-93BW 23°C/50%R.H.	g/m ² x24hrs	10000	
M.V.T.	JIS L1099-1993 A-1(CaCl ₂)40 °C 90% R.H.	g/m ² x24hrs	2500	
W.P.R.	JIS L1092-1998 B Method	mmH ₂ O	10000	
Specific Gravity	ASTM D792		1.23	
Elongation	ASTM D882	%	350	
PE Carrier			Yes	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616