

## Ding Zing® Film FS1008

### Features

- Polyurethane polyester base
- Excellent chemical resistance
- Excellent durability
- Wide processing window
- Superior resistance to oil
- Excellent abrasion resistance

### Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		92 ±3	
Specific Gravity		ASTM D792		1.21	
Tensile Strength	Kg/cm <sup>2</sup>	ASTM D412	MD CD	360 350	
Elongation	%	ASTM D412	MD CD	465 440	
300% Modulus	Kg/cm <sup>2</sup>	ASTM D412	MD CD	130 140	
Tear Strength	Kg/cm	ASTM D624	MD CD	130 130	
Film Melting Point	°C			135	
UV stability	Grade	ASTM D1148		1~2	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

<http://www.dingzing.com> e-mail: [film@dingzing.com.tw](mailto:film@dingzing.com.tw) Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616