

Ding Zing® Film **FS1035**

Features

- Polyurethane polyester base
- Good recovery; rubber-like elasticity
- Outstanding tensile strength
- Easy for processing
- Soft hand
- Excellent durability
- Remarkable abrasion resistance

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		74 ±3	
Specific Gravity		ASTM D792		1.17	
Tensile Strength	Kg/cm ²	ASTM D412	MD CD	404 389	
Elongation	%	ASTM D412	MD CD	736 740	
300% Modulus	Kg/cm ²	ASTM D412	MD CD	43 43	
Tear Strength	Kg/cm	ASTM D624	MD CD	87 83	
Film Melting Point	°C			125	
UV stability	Grade	D1148		4	

** Actual results may yield up to ±15%

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616