

## Ding Zing® Film FS4078

### Features

- Polyurethane polyester base
- Excellent resistance to chemicals
- Good transparency
- High tensile strength
- Excellent elasticity and recovery
- Excellent flexibility at low temperature
- Excellent resistance to aging

### Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		75 ±3	
Specific Gravity		ASTM D792		1.19	
Tensile Strength	Kg/cm <sup>2</sup>	ASTM D412	MD	355	
			CD	375	
Elongation	%	ASTM D412	MD	480	
			CD	505	
300% Modulus	Kg/cm <sup>2</sup>	ASTM D412	MD	70	
			CD	60	
Tear Strength	Kg/cm	ASTM D624	MD	75	
			CD	80	
Film Melting Point	°C			105	
UV stability	Grade	D1148		4	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

<http://www.dingzing.com> e-mail: [film@dingzing.com.tw](mailto:film@dingzing.com.tw) Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616