

## Ding Zing® Film FT1039

### Features

- Polyurethane polyether base
- Excellent low temperature flexibility
- Excellent hydrolysis resistance
- Anti-microbial

### Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		82 ±3	
Specific Gravity		ASTM D792		1.13	
Tensile Strength	Kg/cm <sup>2</sup>	ASTM D412	MD	345	
			CD	335	
Elongation	%	ASTM D412	MD	635	
			CD	690	
300% Modulus	Kg/cm <sup>2</sup>	ASTM D412	MD	70	
			CD	65	
Tear Strength	Kg/cm	ASTM D624	MD	105	
			CD	105	
Film Melting Point	°C			130	
UV stability	Grade	D1148		3	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

<http://www.dingzing.com> e-mail: [film@dingzing.com.tw](mailto:film@dingzing.com.tw) Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616