

Ding Zing® Film FT1081S

Features

- Polyurethane polyether base
- Good waterproof characteristic/
high M.V.T. rate
- Soft touch
- White matte
- Hydrophilic structure
- Outstanding low temperature flexibility
- Excellent resistance to hydrolysis

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		80 ±3	
Specific Gravity		ASTM D792		1.24	
Tensile Strength	Kg/cm ²	ASTM D412	MD	135	
			CD	128	
Elongation	%	ASTM D412	MD	521	
			CD	531	
300% Modulus	Kg/cm ²	ASTM D412	MD	103	
			CD	96	
Tear Strength	Kg/cm	ASTM D624	MD	79	
			CD	74	
Film Melting Point	°C			132	
UV stability	Grade	ASTM D1148		2	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616