

Ding Zing® Film FTA4073

Features

- Polyurethane polyether base
- Excellent hydrolysis resistance
- Good for applications where weatherability and appearance maintenance are critical
- Exceptional UV stability
- Good color and clarity retention

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		85±3	
Specific Gravity		ASTM D792		1.06	
Tensile Strength	Kg/cm ²	ASTM D882	MD	762	
			CD	805	
Elongation	%	ASTM D882	MD	408	
			CD	413	
300% Modulus	Kg/cm ²	ASTM D882	MD	386	
			CD	380	
Tear Strength	Kg/cm	ASTM D624	MD	170	
			CD	173	
Film Melting Point	°C			95	
UV stability	Grade	ASTM D1148		--	

**Actual results may yield up to ± 15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616