

Ding Zing® Film FTA6123

Features

- Optical aliphatic ether product
- Outstanding UV stability
- Able to be used as interlayer in the lamination to different materials
- With excellent transparency
- Very good adhesion to glass, PC, acrylic and other dissimilar materials

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		80±3	
Specific Gravity		ASTM D792		1.07	
Tensile Strength	Kg/cm ²	ASTM D882	MD	413	
			CD	398	
Elongation	%	ASTM D882	MD	514	
			CD	522	
300% Modulus	Kg/cm ²	ASTM D882	MD	59	
			CD	58	
Tear Strength	Kg/cm	ASTM D624	MD	49	
			CD	44	
Film Melting Point	°C			73	
UV stability	Grade	ASTM D1148		--	

**Actual results may yield up to ± 15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616