

Ding Zing® Film FS1713-PE

Features

- Polyurethane polyester base
- Environmentally friendly; containing no plasticizer
- Easy adhesion can be achieved with low temperature
- With very good adhesion

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore D	ASTM D2240		40 ± 2	
Specific Gravity		ASTM D792		1.20	
Tensile Strength	Kg/cm ²	ASTM D412	MD	313	
			CD	378	
Elongation	%	ASTM D412	MD	736	
			CD	863	
300% Modulus	Kg/cm ²	ASTM D412	MD	70	
			CD	64	
Tear Strength	Kg/cm	ASTM D624	MD	98	
			CD	98	
Film Melting Point	°C			40	
UV stability	Grade	ASTM D1148		--	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616