

Ding Zing® Film FS8088

Features

- Polyurethane polyester base
- Superior transparency
- Easy for printing
- Very good low temperature flexibility
- DZ Sparkling Series
- Smooth and glossy
- Easy for high frequency welding

Physical Properties

| *Properties | Unit | Method | Direction | **Value | Note |
|--------------------|--------------------|------------|-----------|------------|------|
| Hardness | Shore A | ASTM D2240 | | 85 ±3 | |
| Specific Gravity | | ASTM D792 | | 1.20 | |
| Tensile Strength | Kg/cm ² | ASTM D412 | MD CD | 430 385 | |
| Elongation | % | ASTM D412 | MD CD | 560 555 | |
| 300% Modulus | Kg/cm ² | ASTM D412 | MD CD | 105 80 | |
| Tear Strength | Kg/cm | ASTM D624 | MD CD | 110 145 | |
| Film Melting Point | °C | | | 125 | |
| UV stability | Grade | D1148 | | 4~5 | |

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616